## NSN 5305-01-304-0635

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-304-0635 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.145 inches **Fastener Length:** 0.310 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.250 inches and 0.262 inches **Head Height:** Between 0.072 inches and 0.082 inches **First Diameter From Head:** Between 0.139 inches and 0.149 inches **Second Diameter From Head:** Between 0.098 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.120 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.165 inches **Point Style:** Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303se **Material Specification:** Astm a581 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-01-304-0635

Externally Relieved Body Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0