## NSN 5305-01-304-1324

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-304-1324 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 0.641 inches and 0.671 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.376 inches and 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.240 inches and 0.260 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Stainless steel **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488 type 2 cl 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: **Unit Of Measure:** 

Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No

## NSN 5305-01-304-1324

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.