## NSN 5305-01-304-5324

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-304-5324
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.438 inches
Fastener Length:
0.625 inches
Head Style:
Hexagon
Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.314 inches
Point Length:
0.100 inches
Point Diameter:
Between 0.142 inches and 0.147 inches
Point Style:
Flat
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Point Chamfer Angle:
45.0 degrees
Special Features:
Two keyways longitudinally opposite each other
Material:
Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or
steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or
steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5305-01-304-5324

Setscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0