NSN 5305-01-304-5770

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-304-5770

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.313 inches and 0.363 inches
Fastener Length:
Between 0.385 inches and 0.415 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.2083 inches and 0.2612 inches
Grip Diameter:
Between 0.1625 inches and 0.1635 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.164 inches
Grip Length:
Between 0.052 inches and 0.072 inches
Thready Qty Per Inch (tpi):
32
Mr. T. att. Organist (c.)
Min. Tensile Strength (psi):
180000 pounds per square inch
180000 pounds per square inch
180000 pounds per square inch Hardness Rating:
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle:
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish:
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material:
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response

opcomodion bata

80205-nas1992 professional/industrial association standard

NSN 5305-01-304-5770

Close Tolerance Screw - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0