## NSN 5305-01-304-6738

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-304-6738 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.375 inches **Fastener Length:** Between 1.940 inches and 2.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.642 inches and 0.656 inches **Head Height:** Between 0.430 inches and 0.437 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.437 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrc

**Specification Data:** 

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-304-6738

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0