

View Online at <https://aerobasegroup.com/nsn/5305-01-304-7935>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.232 inches and 1.311 inches

**Fastener Length:**

Between 1.296 inches and 1.343 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Hole Diameter:**

Between 0.060 inches and 0.080 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

3

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Head Hole Configuration Style:**

Hexagon corners

**Bearing Surface Of Head Surface Finish:**

63.0 microinches

**Shank Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1802 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0