## NSN 5305-01-304-8718

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-304-8718

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.553 inches and 0.625 inches
Fastener Length:  Between 0.595 inches and 0.625 inches
Head Style:  Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.094 inches and 0.095 inches
Thready Qty Per Inch (tpi):
48
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c fastener and 45.0 rockwell c fastener
Minimum Yield Strength:
155000 pounds per square inch
Product Name:
Navy special project
Material:
Steel fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification single treatment response fastener
Thread Series Designator:
Unrf
Specification Data:
90205 pact 251 professional/industrial association standard

## NSN 5305-01-304-8718

Socket Head Cap Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0