Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-305-2569

2a Thread Direction: Right-hand Thread Length: 2.000 inches Fastener Length: 2.000 inches Head Style: Hexagon Head Height:
Right-hand Thread Length: 2.000 inches Fastener Length: 2.000 inches Head Style: Hexagon
Thread Length: 2.000 inches Fastener Length: 2.000 inches Head Style: Hexagon
2.000 inches Fastener Length: 2.000 inches Head Style: Hexagon
Fastener Length: 2.000 inches Head Style: Hexagon
2.000 inches Head Style: Hexagon
Head Style: Hexagon
Hexagon
-
Head Height:
Between 0.455 inches and 0.483 inches
Width Between Flats:
1.125 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.750 inches
Width Across Flats:
0.625 inches
Thready Qty Per Inch (tpi):
10
Min. Tensile Strength (psi):
80000 pounds per square inch
Criticality Code Justification:
Zzzx
Material:
Nickel alloy
Material Specification:
Qq-n-281 federal specification single material response
Thread Series Designator:
Unc
Specification Or Standard:
4 type
Departure From Cited Designator:
Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-305-2569

Socket Head Cap Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-dtl-1222 spec.