Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-305-2572

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.875 inches |
| Fastener Length: |
| Between 0.970 inches and 1.000 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.303 inches and 0.312 inches |
| Head Height: |
| Between 0.185 inches and 0.190 inches |
| Hole Diameter: |
| Between 0.044 inches and 0.050 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.190 inches |
| Width Across Flats: |
| Between 0.1562 inches and 0.1587 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 33.0 rockwell c and 42.0 rockwell c |
| Hole Configuration Style: |
| Round internal hexagon |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |

NSN 5305-01-305-2572

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0