NSN 5305-01-305-2574

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-305-2574 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.506 inches and 0.556 inches **Fastener Length:** Between 0.828 inches and 0.858 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.302 inches and 0.322 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Stainless steel **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488 type 2 cl 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-305-2574

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.