

View Online at <https://aerobasegroup.com/nsn/5305-01-305-5515>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.262 inches and 0.375 inches

Fastener Length:

Between 0.345 inches and 0.375 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.303 inches and 0.312 inches

Head Height:

Between 0.185 inches and 0.190 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

Between 0.156 inches and 0.159 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp xm-7 fastener

Material Specification:

Astm a493 assn standard all material responses fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0