

View Online at <https://aerobasegroup.com/nsn/5305-01-305-6171>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.750 inches

Fastener Length:

Between 2.190 inches and 2.250 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.921 inches and 0.937 inches

Head Height:

Between 0.740 inches and 0.750 inches

Hole Diameter:

Between 0.061 inches and 0.067 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Width Across Flats:

Between 0.500 inches and 0.505 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

170000 pounds per square inch

Hardness Rating:

37.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

150000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0