# NSN 5305-01-305-6308

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-305-6308



# Thread Class:

3a

Thread Direction:

Right-hand

### Thread Length:

Between 1.116 inches and 1.239 inches

#### Fastener Length:

Between 1.224 inches and 1.271 inches

#### Head Style:

Hexagon

Head Height:

Between 0.141 inches and 0.164 inches

#### Width Between Flats:

Between 0.243 inches and 0.251 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.164 inches

### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

## Screw Material:

Iron alloy 660

#### **Screw Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### **Screw Surface Treatment:**

Passivate

#### Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### Bearing Surface Of Head Surface Finish:

63.0 microinches

## Thread Surface Finish:

32.0 microinches

## **Thread Series Designator:**

Unjc

#### Specification Data:

80205-nas1802 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5305-01-305-6308

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

