

View Online at <https://aerobasegroup.com/nsn/5305-01-305-9199>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.670 inches and 1.750 inches

Fastener Length:

Between 3.920 inches and 4.000 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.735 inches and 0.750 inches

Head Height:

Between 0.492 inches and 0.500 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.500 inches

Width Across Flats:

Between 0.375 inches and 0.379 inches

Thready Qty Per Inch (tpi):

13

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Criticality Code Justification:

Zzzw

Material:

Steel

Surface Treatment:

Chromium

Surface Treatment Specification:

Mil-c-23422 military specification single treatment response

Thread Series Designator:

Unc

Departure From Cited Document:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-23422 spec.