

View Online at <https://aerobasegroup.com/nsn/5305-01-306-1622>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.734 inches and 0.875 inches

**Fastener Length:**

Between 0.845 inches and 0.875 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.921 inches and 0.937 inches

**Head Height:**

Between 0.616 inches and 0.625 inches

**Hole Diameter:**

Between 0.061 inches and 0.067 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.625 inches

**Width Across Flats:**

Between 0.5000 inches and 0.5050 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

37.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

150000 pounds per square inch

**Hole Configuration Style:**

Round internal hexagon

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0