NSN 5305-01-306-1622

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-306-1622



| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.734 inches and 0.875 inches |
| Fastener Length: |
| Between 0.845 inches and 0.875 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.921 inches and 0.937 inches |
| Head Height: |
| Between 0.616 inches and 0.625 inches |
| Hole Diameter: |
| Between 0.061 inches and 0.067 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.625 inches |
| Width Across Flats: |
| Between 0.5000 inches and 0.5050 inches |
| Hole Quantity: |
| 6 |
| Ноје Туре: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 170000 pounds per square inch |
| Hardness Rating: |
| 37.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 150000 pounds per square inch |
| Hole Configuration Style: |
| Round internal hexagon |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |

Qq-p-416 type 2 cl 2 federal specification single treatment response

NSN 5305-01-306-1622

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0