## NSN 5305-01-306-3628

Machine Screw - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5305-01-306-3628

| View Online at https://aerobasegroup.com/nsn/5305-01-306-3628   |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.419 inches and 0.500 inches   |
| Fastener Length:  |
| Between 0.469 inches and 0.500 inches   |
| Head Style:   |
| Fillister   |
| Head Diameter:  |
| Between 0.178 inches and 0.183 inches   |
| Head Height:  |
| Between 0.059 inches and 0.069 inches   |
| Internal Drive Style:   |
| Cross recess type 1   |
| Thread Diameter:  |
| 0.112 inches  |
| Thready Qty Per Inch (tpi):   |
| 40  |
| Min. Tensile Strength (psi):  |
| 160000 pounds per square inch   |
| Product Name:   |
| Navy special project  |
| Screw Material:   |
| Steel comp e4340 or steel comp 4140 or steel comp 8740  |
| Screw Material Specification:   |
| Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military |
| specification 3rd material response   |
| Screw Surface Treatment:  |
| Cadmium and chromate  |
| Screw Surface Treatment Specification:  |
| Qq-p-416 ty2 cl2 federal specification single treatment response  |
| Bearing Surface Of Head Surface Finish:   |
| 32.0 microinches  |
| Shank Surface Finish:   |
| 32.0 microinches  |
| Thread Surface Finish:  |
| 32.0 microinches  |
| Thread Series Designator:   |
| Unjc  |
| Shelf Life:   |

## NSN 5305-01-306-3628

Machine Screw - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.