

View Online at <https://aerobasegroup.com/nsn/5305-01-306-3630>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.389 inches and 0.482 inches

**Fastener Length:**

Between 0.531 inches and 0.562 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.371 inches and 0.385 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740

**Screw Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Shank Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5000 spec.