## NSN 5305-01-306-4845

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-306-4845

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.750 inches and 2.125 inches
Fastener Length:
Between 2.065 inches and 2.125 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.937 inches
Head Height:
Between 0.616 inches and 0.625 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
Between 0.5000 inches and 0.5050 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 45.0 rockwell c
Hole Configuration Style:
Round
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unrf

## NSN 5305-01-306-4845

Socket Head Cap Screw - Page 2 of 2



**Specification Data:** 

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0