## NSN 5305-01-307-1821

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-307-1821 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.139 inches and 1.250 inches **Fastener Length:** Between 1.210 inches and 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Color: Gray Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Surface Treatment:** Ceramic **Surface Treatment Specification:** Mil-c-81751, type 1 cl 4 military specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-307-1821

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81751 spec.