## NSN 5305-01-307-5034

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-307-5034 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.635 inches and 0.665 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.516 inches and 0.546 inches **Head Height:** Between 0.585 inches and 0.615 inches **Internal Drive Style:** Hexagon **End Application:** Low altitude navigation & targeting infrared system **Material Accommodated Thickness:** Between 0.280 inches and 0.341 inches **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.173 inches and 0.203 inches Thready Qty Per Inch (tpi): 28 Material: Steel comp 302 spring **Material Specification:** Qq-a-225/8 federal specification single material response stand-off **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A003b0

## NSN 5305-01-307-5034

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-5059 spec.