## NSN 5305-01-307-5883

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-307-5883 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.448 inches **Fastener Length:** Between 1.203 inches and 1.250 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.376 inches and 0.381 inches **Head Height:** Between 0.044 inches and 0.046 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.802 inches and 0.822 inches **Features Provided:** O ring and dry film lubricant and cetyl alcohol lubricant Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Thread Series Designator:** Unjf

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5305-01-307-5883

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0