## NSN 5305-01-307-7893

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-307-7893 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.120 inches **Fastener Length:** 0.890 inches **Head Style:** Flat chamfer **Head Diameter:** 0.500 inches **Head Height:** 0.130 inches **First Diameter From Head:** Between 0.246 inches and 0.248 inches **Second Diameter From Head:** 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.383 inches and 0.387 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.503 inches and 0.507 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 304 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-01-307-7893

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0