NSN 5305-01-307-7894



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-307-7894 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.318 inches and 0.338 inches Fastener Length: 0.560 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.096 inches and 0.106 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.222 inches and 0.242 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

Demilitarization:

Unit Of Measure:

N/a

NSN 5305-01-307-7894

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0