# NSN 5305-01-308-0172

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-0172

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.400 inches

### Fastener Length:

1.200 inches

#### Head Style:

Hexagon

## Head Height:

Between 0.172 inches and 0.190 inches

#### Width Between Flats:

Between 0.428 inches and 0.438 inches

### Internal Drive Style:

W/o internal drive

### Material Accommodated Thickness:

Between 0.501 inches and 0.562 inches

#### **Thread Diameter:**

0.250 inches

## Thready Qty Per Inch (tpi):

28

### Hardness Rating:

36.0 rockwell c fastener and 43.0 rockwell c fastener

### **Special Features:**

Washer under head; thickness 0.015 in. Min 0.035 in. Max

#### Color:

Black stand-off

#### Material:

Steel comp 630 fastener

### **Material Specification:**

Astm a493 assn standard all material responses stand-off

#### **Surface Treatment:**

Oxide stand-off

### Surface Treatment Specification:

Mil-c-13924 cl 2 military specification single treatment response stand-off

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5305-01-308-0172

Panel Screw Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.