## NSN 5305-01-308-0172

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-0172 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.400 inches **Fastener Length:** 1.200 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.428 inches and 0.438 inches **Internal Drive Style:** W/o internal drive **Material Accommodated Thickness:** Between 0.501 inches and 0.562 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 36.0 rockwell c fastener and 43.0 rockwell c fastener **Special Features:** Washer under head; thickness 0.015 in. Min 0.035 in. Max Color: Black stand-off Material: Steel comp 630 fastener **Material Specification:** Astm a493 assn standard all material responses stand-off **Surface Treatment:** Oxide stand-off **Surface Treatment Specification:** Mil-c-13924 cl 2 military specification single treatment response stand-off **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-308-0172

Panel Screw Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.