NSN 5305-01-308-2913

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-2913

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.656 inches |
| Fastener Length: |
| Between 1.516 inches and 1.546 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| 0.8884 inches |
| Grip Diameter: |
| |
| Between 0.4360 inches and 0.4370 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.4375 inches |
| Grip Length: |
| Between 0.865 inches and 0.885 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 4140 |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, ty ii, cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas587 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |

NSN 5305-01-308-2913

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

