## NSN 5305-01-308-2914

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-2914 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.656 inches **Fastener Length:** Between 1.516 inches and 1.546 inches **Head Style:** Flat countersunk **Head Diameter:** 0.8884 inches **Grip Diameter:** Between 0.4672 inches and 0.4682 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.4375 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4140 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty ii, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1607 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-308-2914

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0