NSN 5305-01-308-2916

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-2916 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.641 inches **Fastener Length:** Between 1.126 inches and 1.156 inches **Head Style:** Flat countersunk **Head Diameter:** 0.7604 inches **Grip Diameter:** Between 0.4047 inches and 0.4057 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.3750 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4140 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty ii, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1606 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-308-2916

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0