

NSN 5305-01-308-3834 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-308-3834 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.125 inches **Fastener Length:** Between 5.190 inches and 5.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches **Hole Quantity: Hole Type:** 

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

**Hardness Rating:** 

39.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

**Hole Configuration Style:** 

Round internal hexagon

Material:

Steel

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416 type 2, cl 2 federal specification single treatment response

## NSN 5305-01-308-3834

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0