NSN 5305-01-308-4306

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-4306

Thread Class:				
2a				
Thread Direction:				
Right-hand				
Thread Length:				
Between 0.282 inches and 0.375 inches				
Fastener Length:				
Between 0.344 inches and 0.375 inches				
Head Style:				
Fillister				
Head Diameter:				
Between 0.250 inches and 0.270 inches				
Head Height:				
Between 0.106 inches and 0.113 inches				
Hole Diameter:				
0.046 inches				
Internal Drive Style:				
Slot				
Thread Diameter:				
0.164 inches				
Hole Quantity:				
1				
Thready Qty Per Inch (tpi):				
32				
Min. Tensile Strength (psi):				
80000 pounds per square inch				
Screw Material:				
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 384				
Screw Material Specification:				
66 federal standard all material responses				
Screw Surface Treatment:				
Ceramic				
Screw Surface Treatment Specification:				
Mil-c-81751 type 1 cl 4 military specification single treatment response				
Head Hole Configuration Style:				
Round				
Color:				
Gray				
Thread Series Designator:				
Unc				
Shelf Life:				
N/a				

NSN 5305-01-308-4306

Machine Screw - Page 2 of 2



ι	Jnit	Of	Measure:
•	,,,,,	•	moudai c.

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-81751 spec.