NSN 5305-01-308-4812

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-4812 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.371 inches and 0.438 inches **Fastener Length:** Between 1.069 inches and 1.116 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mac ps13145 fscm 76301 mfr ref all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-308-4812

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0