

View Online at <https://aerobasegroup.com/nsn/5305-01-308-5032>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.775 inches

**Fastener Length:**

1.062 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**Point Length:**

0.100 inches

**Point Diameter:**

Between 0.142 inches and 0.147 inches

**Point Style:**

Flat

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Point Chamfer Angle:**

45.0 degrees

**Special Features:**

Two slots on screw 0.044 in. Min, 0.054 in. Maximum w; 0.982 in. Maximum lg

**Material:**

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347

**Material Specification:**

Qq-s-763 federal specification all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0