Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-6047

	v Online at https://aerobasegroup.com/nsn/5305-01-308-6047
Thr	ead Class:
3a	
Thr	ead Direction:
Rigi	nt-hand
Thr	ead Length:
0.87	'5 inches
Fas	tener Length:
Betv	veen 1.210 inches and 1.250 inches
Неа	d Style:
Flat	chamfer
Hea	d Diameter:
Betv	veen 0.262 inches and 0.270 inches
Hea	d Height:
Betv	veen 0.159 inches and 0.164 inches
Inte	rnal Drive Style:
Hex	agon
Thr	ead Diameter:
0.16	34 inches
Wid	th Across Flats:
Betv	veen 0.1406 inches and 0.1426 inches
Thr	eady Qty Per Inch (tpi):
32	
Col	or:
Gra	y
Mat	erial:
Stee	el comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Mat	erial Specification:
Astr	n a493 assn standard all material responses
Sur	face Treatment:
Cer	amic
Sur	face Treatment Specification:
Mil-	c-81751 ty1 cl4 military specification single treatment response
Thr	ead Series Designator:
Unr	
She	If Life:
N/a	
Uni	t Of Measure:
Den	nilitarization:
No	
Fiig	:
A00	3b0

NSN 5305-01-308-6047

Socket Head Cap Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-81751 spec.

