Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-6048

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.875 inches
Fastener Length:
Between 1.460 inches and 1.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.141 inches and 0.143 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Color:
Gray
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Material Specification:
Astm a493 assn standard all material responses
Surface Treatment:
Ceramic
Surface Treatment Specification:
Mil-c-81751 type 1, cl 4 military specification single treatment response
Thread Series Designator:
Unrc

Shelf Life:

N/a

NSN 5305-01-308-6048

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81751 spec.

