NSN 5305-01-308-6202



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-308-6202 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.532 inches and 0.625 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.106 inches and 0.113 inches **Hole Diameter:** 0.046 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Ceramic **Screw Surface Treatment Specification:** Mil-c-81751 type 1, cl 4 military specification single treatment response **Head Hole Configuration Style:** Round Color:

Gray **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-01-308-6202

Machine Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-81751 spec.