## NSN 5305-01-308-9183

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-308-9183 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.283 inches and 0.323 inches **Fastener Length:** Between 0.365 inches and 0.385 inches **Head Style:** Hexagon **Head Height:** Between 0.106 inches and 0.118 inches Width Between Flats: Between 0.305 inches and 0.313 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 36 **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8740 **Screw Material Specification:** Ams 6322 assn standard single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Ams 2495 assn standard single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Special Features:** Without internal drive Color: Black **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5305-01-308-9183

Machine Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A500d0