

View Online at <https://aerobasegroup.com/nsn/5305-01-309-5457>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.276 inches

Fastener Length:

Between 0.949 inches and 0.979 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.328 inches and 0.337 inches

Grip Diameter:

Between 0.1621 inches and 0.1627 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.164 inches

Grip Length:

Between 0.673 inches and 0.703 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp 4340

Material Specification:

Mil-s-5626 military standard all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1152 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.