

View Online at <https://aerobasegroup.com/nsn/5305-01-309-7236>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.523 inches and 0.625 inches

Fastener Length:

Between 0.594 inches and 0.625 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.367 inches and 0.375 inches

Head Height:

Between 0.133 inches and 0.150 inches

Hole Diameter:

Between 0.060 inches and 0.068 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.250 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response

Head Hole Configuration Style:

Round

Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjf

Specification Data:

80205-nas1101 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.