Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-309-7717

Thread Class:
3a
Sa Thread Direction:
Right-hand
Thread Length:
0.875 inches
Fastener Length:
Between 3.440 inches and 3.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-309-7717

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

