NSN 5305-01-310-1665

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-310-1665 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.478 inches and 1.640 inches **Fastener Length:** Between 1.688 inches and 1.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.477 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response Color: Black **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 3c style Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-310-1665

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.