## NSN 5305-01-310-4566

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-310-4566 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.476 inches and 0.526 inches **Fastener Length:** Between 1.111 inches and 1.141 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.4289 inches and 0.4787 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

**Specification Data:** 

80205-nas1581 professional/industrial association standard

--

## NSN 5305-01-310-4566

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0