NSN 5305-01-310-5248

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-310-5248 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.500 inches and 1.727 inches **Fastener Length:** Between 4.156 inches and 4.250 inches **Head Style:** Hexagon **Head Height:** Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches **Hole Diameter:** Between 0.092 inches and 0.100 inches **Thread Diameter:** 0.625 inches **Hole Quantity: Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 120000 pounds per square inch **Hardness Rating:** 25.0 rockwell c and 34.0 rockwell c **Hole Configuration Style:** Hexagon flats Material: Steel **Material Specification:** Sae gr 5 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unc

NSN 5305-01-310-5248

Hexagon Head Cap Screw - Page 2 of 2



| Sp | ecific | ation | Or S | Stand | lard: |
|----|--------|-------|------|-------|-------|
|----|--------|-------|------|-------|-------|

2 type and 10p style and 5 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0