

View Online at <https://aerobasegroup.com/nsn/5305-01-310-9244>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.258 inches and 1.500 inches

Fastener Length:

Between 1.440 inches and 1.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.921 inches and 0.938 inches

Head Height:

Between 0.616 inches and 0.625 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Width Across Flats:

Between 0.500 inches and 0.505 inches

Thready Qty Per Inch (tpi):

11

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Color:

Black

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

66 federal standard all material responses

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.