Socket Head Cap Screw - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5305-01-310-9245

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.085 inches and 1.170 inches
Fastener Length:
Between 1.710 inches and 1.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.457 inches and 0.469 inches
Head Height:
Between 0.306 inches and 0.313 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.250 inches and 0.253 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Color:
Black
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924 cl 4 military specification single treatment response
Thread Series Designator:
Unc

Unc

Specification Or Standard:

1 type

NSN 5305-01-310-9245

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.

