NSN 5305-01-310-9248

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-310-9248 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.644 inches and 0.674 inches **Fastener Length:** Between 1.082 inches and 1.112 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.717 inches and 0.760 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** 100.0 degrees Material: Steel **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas672 assn standard single treatment response

Thread Series Designator: Unjf Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-310-9248

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0