NSN 5305-01-310-9508

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-310-9508



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.380 inches and 0.410 inches

Fastener Length:

Between 0.850 inches and 0.880 inches

Head Style:

Round extended washer

Head Diameter:

0.437 inches

Head Height:

Between 0.096 inches and 0.106 inches

Extended Washer Diameter:

0.500 inches

Extended Washer Thickness:

Between 0.028 inches and 0.033 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Screw Material:

Steel comp 4037 or steel comp 8630

Screw Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 type 2 class 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-310-9508

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

