NSN 5305-01-310-9992

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-310-9992 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** Between 1.210 inches and 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** Between 0.083 inches and 0.086 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.0781 inches and 0.0791 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-310-9992

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0