

View Online at <https://aerobasegroup.com/nsn/5305-01-311-0935>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.363 inches

Fastener Length:

Between 2.098 inches and 2.128 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.339 inches and 0.381 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Internal Drive Style:

Torque-set ribbed

Thread Diameter:

0.190 inches

Grip Length:

Between 1.740 inches and 1.760 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.972 inches first hole and 2.022 inches first hole

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1580 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0