NSN 5305-01-311-6246

Shoulder Screw - Page 1 of 2

3a

View Online at https://aerobasegroup.com/nsn/5305-01-311-6246



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.720 inches and 0.750 inches Fastener Length: Between 5.720 inches and 5.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.853 inches and 0.875 inches **Head Height:** Between 0.365 inches and 0.375 inches **Shoulder Diameter:** 0.621 inches first shoulder and 0.623 inches first shoulder Shoulder Length: 4.495 inches first shoulder and 5.005 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 13 Hardness Rating: 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4340 or steel comp e4340 **Material Specification:** Ams 6415 assn standard 1st material response or mil-s-5000 military specification 2nd material response **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

NSN 5305-01-311-6246

Shoulder Screw - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

